



銓誼實業有限公司
CHUAN YI ENTERPRISES CO., LTD.

PR - X - X X - X X X X X X X X X X
1 2 3 4 5 6 7 8 9

1 : Contact Type

D = Straight Dip
R = Right Angle
S = Solder

2 : Performance

1A = 10 AMP
2A = 20 AMP
3A = 30 AMP
4A = 40 AMP

3 : Size/Number of Positions

1W1	3V3	5W5	7W7	24W7
2V2	3W3	9W4	8W8	36W4
2W2	7W2	13W3	13W6	43W2
5W1	11W1	17W2	17W5	47W1
		21W1	21W4	
			25W3	
			27W2	

4 : Connector/Pin Type

P = Plug (male)
S = Socket (female)

5 : Insulator Color

0 = Black
1 = White
2 = Green
3 = Blue

6 : Contact Plating

0 = Full gold flash
1 = 5u" Gold Plating
2 = 15u" Gold Plating
3 = 30u" Gold Plating
4 = 50u" Gold Plating

7 : Shell Type

- 0 = Tin Plated
- 1 = Nickel Plated
- 2 = Chromate Plated

8 : Accessories

- Blank = No Accessories
- U1 = #4-40UNC - 8.6 Short L-Shape Bracket (L 支架)
- U2 = #4-40UNC - 8.6 Short L-Shape Bracket + Boardlock (L 支架帶魚叉)
- U3 = #4-40UNC - 10.6 Long L-Shape Bracket (L 支架)
- U4 = #4-40UNC - 10.6 Long L-Shape Bracket+Boardlock (L 支架帶魚叉)
- U5 = #4-40UNC - L-Shape Bracket Single Piece (菁英L支架)
- U6 = #4-40UNC - Rear Rivet (後卯銅柱)
- U7 = #4-40UNC - Front Rivet (前卯銅柱)
- U8 = #4-40UNC - Boardlock Rivet (魚叉銅柱)
- U9 = #4-40UNC - 9.6 Short L-Shape Bracket (L 支架)
- U10 = #4-40UNC - 9.6 Short L-Shape Bracket + Boardlock (L 支架帶魚叉)
- U11 = #4-40UNC - 11.6 Long L-Shape Bracket (L 支架)
- U12 = #4-40UNC - 11.6 Long L-Shape Bracket+Boardlock (L 支架帶魚叉)

- M1 = M3 - 8.6 Short L-Shape Bracket (L 支架)
- M2 = M3 - 8.6 Short L-Shape Bracket + Boardlock (L 支架帶魚叉)
- M3 = M3 - 11.6 Long L-Shape Bracket (L 支架)
- M4 = M3 - 11.6 Long L-Shape Bracket+Boardlock (L 支架帶魚叉)
- M5 = M3 - L-Shape Bracket Single Piece (菁英L支架)
- M6 = M3 - Rear Rivet (後卯銅柱)
- M7 = M3 - Front Rivet (前卯銅柱)
- M8 = M3 - Boardlock Rivet (魚叉銅柱)
- M9 = M3 - 9.6 Short L-Shape Bracket (L 支架)
- M10 = M3 - 9.6 Short L-Shape Bracket + Boardlock (L 支架帶魚叉)
- M11 = M3 - 10.6 Long L-Shape Bracket (L 支架)
- M12 = M3 - 10.6 Long L-Shape Bracket+Boardlock (L 支架帶魚叉)

9 : Material of Insulator

- Blank = PBT
- P6 = PA6T